




MODL.VARIO insert for coupling housing type B

B-code M12, female, shielded

Insert - mobile housing  
Female straight – male straight  
M12, 4-pole  
B-coded  
Good chemical and oil resistance (oil resistance does not apply to use with PVC cable)  
The resistance to aggressive media should be individually tested for your application. Further details on request.

Odkaz k produktu

Obrázky



Výrobok sa môže líšiť od zobrazenia

| Side 1                   |              |
|--------------------------|--------------|
| Family construction form | M12          |
| Coding                   | B            |
| Material contact         | Copper alloy |
| No. of poles             | 4            |
| Side 2                   |              |
| Family construction form | M12          |
| Coding                   | B            |
| Material contact         | Copper alloy |

No. of poles 4

| Commercial data       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27260702      |
| ECLASS-6.1            | 27279221      |
| ECLASS-7.0            | 27440104      |
| ECLASS-8.0            | 27440104      |
| ECLASS-9.0            | 27440106      |
| ECLASS-10.1           | 27440106      |
| ECLASS-11.1           | 27440106      |
| ECLASS-12.0           | 27440106      |
| ETIM-5.0              | EC001855      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879576505 |
| Packaging unit        | 1             |

| Electrical data   Supply           |      |
|------------------------------------|------|
| Operating voltage AC max.          | 49 V |
| Operating voltage DC max.          | 49 V |
| Current operating per contact max. | 4 A  |

| Diagnostics           |    |
|-----------------------|----|
| Status indication LED | no |

| Installation   Connection |         |
|---------------------------|---------|
| Tightening torque         | 0,6 Nm  |
| Mounting set              | M12 x 1 |

| Device protection   Electrical         |                   |
|----------------------------------------|-------------------|
| Degree of protection (EN IEC 60529)    | IP65, IP67        |
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 1,5 kV            |
| Material group (IEC 60664-1)           | I                 |

| Mechanical data             |         |
|-----------------------------|---------|
| Contour for corrugated hose | without |

| Mechanical data   Material data |               |
|---------------------------------|---------------|
| Coating housing                 | nickel plated |
| Coating contact                 | gold plated   |
| Material gasket                 | FKM           |
| Material housing                | Brass         |

| Mechanical data   Mounting data |                                       |
|---------------------------------|---------------------------------------|
| Mounting method                 | inserted, screwed, Shaking protection |

| Environmental characteristics   Climatic |        |
|------------------------------------------|--------|
| Operating temperature min.               | -25 °C |
| Operating temperature max.               | 85 °C  |

| Conformity       |                          |
|------------------|--------------------------|
| Product standard | DIN EN 61076-2-101 (M12) |