

T-Coupler M12 female / M12 male + female B-cod.

5-pol., Profibus

T-coupler

Female straight – female/male straight



M12 – M12, 5-pole

B-coded


shielded

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Odkaz k produktu**Obrázky**

Výrobok sa môže líšiť od zobrazenia

**Side 1**

Family construction form	M12
Coding	B
No. of poles	5

Width across flats SW13

Side 2

Family construction form M12

Coding B

No. of poles 5

Side 3

Family construction form M12

Coding B

Commercial data

ECLASS-6.0 27143423

ECLASS-6.1 27279221

ECLASS-7.0 27440104

ECLASS-8.0 27440104

ECLASS-9.0 27440106

ECLASS-10.1 27440106

ECLASS-11.1 27440106

ECLASS-12.0 27440106

ETIM-5.0 EC001855

customs tariff number 85366990

GTIN 4048879141406

Packaging unit 1

Electrical data | Supply

Operating voltage DC 5 V

Current operating per contact max. 0,0125 A

Industrial communication

Data transmission rate max. 12 MBit/s

Installation | Connection

Tightening torque 0,6 Nm

Mounting set M12 x 1

Device protection | Electrical

Degree of protection (EN IEC 60529) IP67

Additional condition protection degree inserted, screwed

Pollution Degree 3

Material group (IEC 60664-1) I

Mechanical data | Material data

Coating locking Nickeled

Locking material Zinc die-casting

Mechanical data | Mounting data

Mounting method inserted, screwed, Shaking protection

Environmental characteristics | Climatic

Operating temperature min. -25 °C

Operating temperature max. 85 °C