

**M12 Power female 0° T-cod. with cable**

PUR 4x1.5 bk UL/CSA+drag ch. 15m

Power

Female straight

M12, 4-pole



T-coded


with cable sleeves

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

**Odkaz k produktu****Obrázky**



Výrobok sa môže líšiť od zobrazenia



Cable length 15 m

#### Side 1

|                                           |              |
|-------------------------------------------|--------------|
| Tightening torque                         | 0,6 Nm       |
| Coating contact                           | gold plated  |
| Family construction form                  | M12P         |
| Thread                                    | M12 x 1      |
| suitable for corrugated tube (internal Ø) | 12 mm        |
| Coding                                    | T            |
| Material contact                          | Copper alloy |
| No. of poles                              | 4            |

#### Side 2

Stripping length (jacket) 100 mm

#### Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27279218      |
| ECLASS-6.1            | 27279218      |
| ECLASS-7.0            | 27279218      |
| ECLASS-8.0            | 27279218      |
| ECLASS-9.0            | 27060327      |
| ECLASS-10.1           | 27060311      |
| ECLASS-11.1           | 27060311      |
| ECLASS-12.0           | 27060327      |
| ETIM-5.0              | EC001855      |
| customs tariff number | 85444290      |
| GTIN                  | 4048879754712 |
| Packaging unit        | 1             |

#### Electrical data | Supply

|                                    |      |
|------------------------------------|------|
| Operating voltage DC max.          | 63 V |
| Current operating per contact max. | 12 A |

#### Diagnostics

|                       |    |
|-----------------------|----|
| Status indication LED | no |
|-----------------------|----|

#### Installation | Connection

|                                                 |                                                                                                   |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Stripping length (jacket)                       | 100 mm                                                                                            |
| Width across flats                              | SW17                                                                                              |
| <b>Device protection   Electrical</b>           |                                                                                                   |
| Degree of protection (EN IEC 60529)             | IP65, IP67                                                                                        |
| Additional condition protection degree          | inserted, screwed                                                                                 |
| Pollution Degree                                | 3                                                                                                 |
| Rated surge voltage                             | 1,5 kV                                                                                            |
| Material group (IEC 60664-1)                    | I                                                                                                 |
| <b>Mechanical data   Material data</b>          |                                                                                                   |
| Coating locking                                 | Nickeled                                                                                          |
| Material gasket                                 | FKM                                                                                               |
| Material housing                                | PUR                                                                                               |
| Locking material                                | Zinc die-casting                                                                                  |
| <b>Mechanical data   Mounting data</b>          |                                                                                                   |
| Mounting method                                 | inserted, screwed, Shaking protection                                                             |
| <b>Environmental characteristics   Climatic</b> |                                                                                                   |
| Operating temperature min.                      | -25 °C                                                                                            |
| Operating temperature max.                      | 85 °C                                                                                             |
| Additional condition temperature range          | depending on cable quality                                                                        |
| <b>Conformity</b>                               |                                                                                                   |
| Product standard                                | IEC 61076-2-111                                                                                   |
| <b>Installation   Cable</b>                     |                                                                                                   |
| Cable identification                            | P07                                                                                               |
| Cable Type                                      | 3                                                                                                 |
| Printing color of wire insulation               | black (white isolation), white (isolation blue), white (isolation brown), white (isolation black) |
| Jacket Color                                    | black                                                                                             |
| Type of Certificate                             | cURus                                                                                             |
| Amount stranding                                | 1                                                                                                 |
| Stranding                                       | 4 wires twisted                                                                                   |
| wire arrangement                                | black 4, blue 3, white 2, brown 1                                                                 |
| Cable weight                                    | 114,4 g/m                                                                                         |
| Material jacket                                 | PUR                                                                                               |
| Shore hardness jacket                           | 90 ± 5 Shore A                                                                                    |
| Freedom from ingredients (jacket)               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                    |
| Outer-diameter (jacket)                         | 7,2 mm                                                                                            |
| Tolerance outer diameter (sheath)               | ± 5 %                                                                                             |
| Material wire insulation                        | PP                                                                                                |
| Amount wires                                    | 4                                                                                                 |
| Outer diameter insulation                       | 2,3 mm                                                                                            |
| Outer diameter tolerance core insulation        | ± 5 %                                                                                             |
| Shore hardness wire insulation                  | 60 ± 5 Shore D                                                                                    |
| Ingredient freeness wire insulation             | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                    |
| Printing color of wire insulation               | black (white isolation), white (isolation blue), white (isolation brown), white (isolation black) |
| Amount strands (wire)                           | 84                                                                                                |
| Diameter of single wires                        | 0,15 mm                                                                                           |
| Conductor crosssection (wire)                   | 1,5 mm²                                                                                           |
| Material conductor wire                         | Stranded copper wire, bare                                                                        |
| Conductor type (wire)                           | strand class 6                                                                                    |
| Traversing distance (C-track)                   | 5 m @ 25 °C                                                                                       |
| Current load capacity (standard)                | to DIN VDE 0298-4                                                                                 |
| Current load capacity min. wire                 | 14,4 A                                                                                            |

|                                                         |                                                      |
|---------------------------------------------------------|------------------------------------------------------|
| Electrical resistance line constant wire                | 13,3 $\Omega$ /km @ 20 °C                            |
| Nominal voltage power AC max.                           | 1000 V                                               |
| Power frequency withstand voltage power (wire - jacket) | 10 kV @ 60 s                                         |
| AC withstand voltage power (wire - wire)                | 10 kV @ 60 s                                         |
| Min. operating temperature (static)                     | -50 °C                                               |
| Max. operating temperature (fixed)                      | 80 °C / 90 °C @ 10000 h Operation                    |
| Operating temperature min. (dynamic)                    | -25 °C                                               |
| Operating temperature max. (dynamic)                    | 80 °C / 90 °C @ 10000 h Operation                    |
| UV resistance                                           | DIN EN ISO 4892-2 A                                  |
| Flame resistance                                        | UL 1581 § 1090   UL 1581 § 1100 FT2   IEC 60332-2-2  |
| chemical resistance                                     | Good, application-related testing                    |
| Gasoline resistance                                     | Good, application-related testing                    |
| Oil resistance                                          | Good, application-related testing   DIN EN 60811-404 |
| No. of bending cycles (C-track)                         | 5 Mio. @ 25 °C                                       |
| Bending radius (fixed)                                  | 7,5 x Outer diameter                                 |
| Bending radius (dynamic)                                | 10 x Outer diameter                                  |
| No. of torsion cycles                                   | 2 Mio. 25 °C                                         |
| Torsion speed                                           | 35 cycles/min                                        |
| Torsion stress                                          | $\pm$ 180 °/m                                        |