

**Pneumatic insert with valve - female, 6 mm**

Pneumatic female

Internal hose Ø

6 mm

Integrated valve

Technical data will be only guaranteed with Murrelektronik components.

**[Odkaz k produktu](#)****Obrázky**

Výrobok sa môže líšiť od zobrazenia

**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27261204      |
| ECLASS-6.1            | 27261290      |
| ECLASS-7.0            | 27440290      |
| ECLASS-8.0            | 27440290      |
| ECLASS-9.0            | 27440220      |
| ECLASS-10.1           | 27440220      |
| ECLASS-11.1           | 27440220      |
| ECLASS-12.0           | 27440220      |
| ETIM-5.0              | EC000438      |
| customs tariff number | 39269097      |
| GTIN                  | 4048879672856 |
| Packaging unit        | 10            |

**Installation | Connection**

|                    |        |
|--------------------|--------|
| Gender             | female |
| Mating cycles min. | 500    |

**Mechanical data**

|                         |       |
|-------------------------|-------|
| Operating pressure max. | 8 bar |
| Integrated valve        | yes   |

**Mechanical data | Material data**

|                  |               |
|------------------|---------------|
| Material housing | Delrin Acetal |
|------------------|---------------|

**Mechanical data | Mounting data**

|                 |      |
|-----------------|------|
| Internal hose Ø | 6 mm |
|-----------------|------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -40 °C |
|----------------------------|--------|

Operating temperature max. 80 °C