

Power Supply Emparro20-Advanced-3-phase

IN: 3x400 - 500VAC; OUT: 70 - 85V/6,7ADC

The Emparro20-Advanced series of three-phase DIN rail power supplies are extremely versatile and are suitable for a wide range of applications where reliable DC power is required. The high efficiency of these power supplies allows you to save on energy costs while reducing your carbon footprint. Thanks to the low heat dissipation, the service life of the power supplies is extended and the cooling requirements of your control cabinet are reduced. The switching power supply also offers a 5-second power boost, which allows the operation of capacitive and inductive loads. With a very low inrush current, the input circuit breaker is prevented from tripping. The push-in terminal technology ensures quick and easy installation of the power supply unit. The powerful overvoltage protection effectively protects the power supplies from short-term voltage spikes, which extends the service life of the power supplies and increases machine availability.

Odkaz k produktu

Obrázky



Výrobok sa môže líšiť od zobrazenia



Commercial data

ECLASS-6.0	27049002
ECLASS-6.1	27049002
ECLASS-7.0	27049002
ECLASS-8.0	27049002
ECLASS-9.0	27040701
ECLASS-10.1	27040701
ECLASS-11.1	27040701
ECLASS-12.0	27040701
ETIM-5.0	EC002540
customs tariff number	85044083
GTIN	4065909055267
Packaging unit	1

Electrical data

Number of devices parallel connection max.	3
Number of devices series connection max.	20
Parallel connection	yes
Series connection	yes

Informácie v tomto produkte PDF boli zostavené s maximálnou starostlivosťou.
Zodpovednosť sa obmedzuje hrubou neobanlivosťou vo vzťahu k správnosti, úplnosti a aktuálnosti. Stav: 10.05.2024

Murrelektronik Slovakia s.r.o. | Mýtna 48 | SK-811 07 Bratislava | Telefón +421 2 57 351 351 | Fax | shop@murrelektronik.sk | shop.murrelektronik.sk

Security level SELV/PELV

Electrical data Input	
Input voltage 1 AC	400 V
Input voltage 2 AC	500 V
Input voltage AC min.	350 V
Input voltage AC max.	575 V
Input current at input voltage 1 AC	0,8 A
Input current at input voltage 2 AC	0,66 A
Phase number input	3
Efficiency	95,7 % @ 400 V AC, 95,5 % @ 500 V AC
Electrical data Output	
Output rating	480 W
Output voltage DC	72 V
Output voltage DC min.	70 V
Output voltage DC max.	85 V
Output current	6,9 A
Duration Power Boost min.	5 s
Mains failure bridging time	24 ms
Power Boost	150 %
Ripple (s-s) max.	50 mV
Spikes (s-s) max.	150 mV
Diagnostics	
Alarm contact	yes
Installation Connection	
Connection	Push-In spring clamp terminals
Device protection Electrical	
Installation height max. ASL	3000 m
Degree of protection (EN IEC 60529)	IP20
Protection class (EN IEC 61140)	I
Overload protection output	yes
Pollution Degree	2
Short-circuit protection output	yes
Overtemperature protection output	yes
Device protection Mechanical	
Cooling type	Natural convection
Mechanical data Material data	
Combustibility class housing (UL94)	V-0
Conformal coated PCB	no
Material housing	Aluminium
Mechanical data Mounting data	
Net weight	1050 g
Mounting method	geschnappt
Suitable for mounting type	Tragschiene TH35-7.5/TH35-15
mounting position	horizontal, vertical
Height	129 mm
Width	65 mm
Depth	159,3 mm
Environmental characteristics Climatic	
Ambient temperature min.	-25 °C
Ambient temperature max.	70 °C

Storage temperature min.	-40 °C
Storage temperature max.	85 °C
Relative humidity max. (operation)	95 %

Environmental product conformity

REACH	(EC) No 1907/2006
REACH-SVHC	compliant
RoHS	2011/65/EU
China RoHS	compliant EPUP 25
WEEE	compliant
Halogen-free-Material	JEDEC JS709A
Pb-free-Material	JESD97

Conformity

CE	2014/30/EU
----	------------

Approvals

UL	E200364
SEMI F47	compliant